Slim Metal Series Analog Clocks

Wi-Fi

Our proven, long-trusted technology synchronizes time across campuses, hospitals, and facilities of any size — enhancing efficiency, reducing delays, and ensuring pinpoint accuracy. With automated daylight saving time adjustments and zero disruption, Primex Sync keeps your organization running on time, all the time.

Primex Sync Slim Metal Series analog clocks feature contemporary frames that offer an upscale, executive look to our high-performance clocks. These high-tech synchronized clocks are easy to install and incorporate seamlessly into any décor. Primex Sync Slim Metal Series analog clocks are available in various colors, sizes, and dial options, including custom dials to showcase your facility name or logo.

Built-in Wi-Fi connectivity that adheres to the latest WiFi standards, utilizing TLS 1.3 encryption. Allows for flexibility in clock location placement and facilitywide expandability. Simply access your existing IT network via Wi-Fi to quickly synchronize to the exact second. With Primex Sync WiFi clocks, no complicated configuration app required. Once the clocks are connected, simply hang on the wall and enjoy.



Slim Metal



Slim Metal
General 12/24



Slim Metal
Healthcare

WIFI SLIM METAL SERIES ANALOG CLOCKS - BATTERY POWERED	
PART NO.	**DESCRIPTION**
126-PE110M01	12.5" (31.75cm) Slim Metal, Wi-Fi, battery powered , Configured
126-PE110M02	12.5" (31.75cm) Slim Metal, Healthcare Dial, Wi-Fi, battery powered, Configured
126-PE110M05	12.5" (31.75cm) Slim Metal, General 12/24 Dial, Wi-Fi, battery powered, Configured
126-PE150M01	16" (40.64cm) Slim Metal, Wi-Fi, battery powered, Configured
126-PE150M02	16" (40.64cm) Slim Metal, Healthcare Dial, Wi-Fi, battery powered, Configured
126-PE150M05	16" (40.64cm) Slim Metal, General 12/24 Dial, Wi-Fi, battery powered, Configured

WIFI SLIM METAL SERIES ANALOG CLOCKS - AC POWERED	
PART NO.	**DESCRIPTION**
126-AS210M01	12.5" (31.75cm) Slim Metal, WiFi, 120/240V with plug connector
126-AS210M02	12.5" (31.75cm) Slim Metal, Healthcare Dial, WiFi, 120/240V with plug connector
126-AS210M05	12.5" (31.75cm) Slim Metal, General Dial, WiFi, 120/240V with plug connector, configured
126-AS250M01	16" (40.64cm) Slim Metal, Standard, WiFi, 120/240V with plug connector, Configured
126-AS250M02	16" (40.64cm) Slim Metal, Healthcare Dial, WiFi, 120/240V with plug connector, Configured
126-AS250M05	16" (40.64cm) Slim Metal, General Dial, WiFi, 120/240V with plug connector, Configured

Dual Clock Kit

Create an easy-to-read dual-sided clock for hallways or other large areas with our Dual Clock Kit. The kit includes a bracket, mounting plate and hardware to easily assemble and install two 12.5" (31.75cm) or 16" (40.64cm) Slim Metal Clocks back-to-back.

DUAL CLOCK KIT	
PART NO.	**DESCRIPTION**
199-000042	12.5" (31.75cm) Dual Mounting Kit - Slim Metal
199-000043	16" (40.64cm) Dual Mounting Kit - Slim Metal



Easy-to-assemble bracket kit lets you create a dual-sided clock for hallways or other large areas.

FEATURES

- Automatically adjusts for Daylight Saving Time
- Clock Lock feature can be used to securely mount to the wall
- Power:
  - AC Models: 120/240v AC with plug connector
- Management:
  Centrally managed through our OneVue platform to check WiFi and time synchronization reception, along with individual clock battery status.
- Connectivity:
  - Wi-Fi 802.11 b/g/n 2.4GHz
  - Clock configuration to access your network is accomplished online prior to delivery for plug-and-play convenience
- Security:
  - Encryption: TLS 1.3

SLIM METAL SERIES SPECIFICATIONS

- Clock power: PoE 802.3 at/af compatible
- Operating range: 32° - 158°F (0° - 70°C)
- **Clock power:**
  - Battery Models: 4 “D” Sized Batteries (Sold Separately)
  - AC Models: 120/240v AC with plug connector
- **Connectivity:**
  - Wi-Fi 802.11 b/g/n 2.4GHz
- **Security:**
  Encryption: TLS 1.3
- **12.5” Slim Metal**
  - 12.5” (31.75cm) diameter
  - Passivated aluminum bezel with thermoplastic lens
  - 2.5” (6.4cm) deep
- **12.5” Dual-Sided Clock Kit** (assembled dimensions)
  - 12.5” (31.75cm) diameter
  - 5.5” (14.0cm) width
  - 14” (35.6cm) projection from mounting surface (wall or ceiling)
- **16” Slim Metal**
  - 16” (40.64cm) diameter
  - Passivated aluminum bezel with thermoplastic lens
  - Single clock depth: 2.8” (7.1cm)
- **16” Dual-Sided Clock Kit (assembled dimensions)**
  - 16” (40.64 cm) diameter
  - 6.4” (16.2 cm) width
  - 18.2” (46.2 cm) projection from mounting surface (wall or ceiling)

LENS

- Durable thermoplastic lenses

DIALS

- Customized clock faces are available to display your organization’s name or logo
- Please call for more information



Battery Models



AC Models: 120/240v AC with plug connector

To Learn More:
Call - 855-602-2934
Email - info@primexinc.com
primexinc.com

©2025 by Primex, Inc.
The Primex logo is a registered trademark of Primex, Inc. All Rights Reserved. 5.14.25