Traditional Series Analog Clocks

PoE (Power over Ethernet)

Our proven, long-trusted technology synchronizes time across campuses, hospitals, and facilities of any size — enhancing efficiency, reducing delays, and ensuring pinpoint accuracy. With automated daylight saving time adjustments and zero disruption, Primex Sync keeps your organization running on time, all the time.

Primex Sync Traditional Series analog clocks feature easy-to-read dials and durable thermoplastic frames and lenses, making them ideal for almost any setting. They are available in a variety of colors, sizes, and dial options, including custom dials to showcase your facility name or logo.

Built in PoE means there is no need for additional power source or batteries, as the cable that carries the time data to the clocks also carries power. Primex Sync PoE clocks are delivered preconfigured, ready to quickly access your existing network. Simply take the clocks out of the box, connect to PoE power (Power over Ethernet), and hang them on the wall. Battery backup allows for continued accurate time even when the power goes out.

POE TRADITIONAL SERIES ANALOG CLOCKS - POE POWERED WITH BATTERY BACKUP	
PART NO.	**DESCRIPTION**
124-PE110A01	12.5" (31.75cm) Black, PoE powered, Configured
124-PE110A05	12.5" (31.75cm) Black, General 12/24 Dial, PoE powered, Configured
124-PE110W01	12.5" (31.75cm) White, PoE powered, Configured
124-PE110W05	12.5" (31.75cm) White, General Dial, PoE powered, Configured
124-PE150A01	16" (40.64cm) Black, PoE powered, Configured
124-PE150A05	16" (40.64cm) Black, 12/24 General Dial, PoE powered, Configured



12.5" or 16"
Traditional Series

Dual Clock Kit

Create an easy-to-read dual-sided clock for hallways or other large areas with our Dual Clock Kit. The kit includes a bracket, mounting plate, and hardware to easily assemble and install two 12.5" (31.75cm) Traditional Series Clocks back-to-back.

DUAL CLOCK KIT	
PART NO.	**DESCRIPTION**
199-000040	12.5" (31.75cm) Dual Mounting Kit
199-000041	12.5" (31.75cm) Dual Mounting Kit - White



12.5" or 16"
Traditional Series
General 12/24



Easy-to-assemble bracket kit lets you create a dual-sided clock for hallways or other large areas.

FEATURES

- Automatically adjusts for Daylight Saving Time
- Clock Lock feature can be used to securely mount to the wall
- Clock configuration to access your network is accomplished online prior to delivery for plug-and-play convenience
- Battery backup allows for continued accurate time even when the power goes out (batteries not included)

Power:
- PoE/Battery Models: IEEE 802.3 PoE at/af PoE+ (Class 0, 2 Watts Peak, 1 Watt Nominal)

Connectivity:
- IEEE 802.3 10/100 Base-T Ethernet

Security:
- Encryption: TLS 1.3

TRADITIONAL SERIES SPECIFICATIONS

- Durable thermoplastic frames and lenses
- 12.5" (31.75cm) or 16" (40.64cm) diameter
- **Clock depth:** 2.5" (6.4cm)
- **Operating range:** 32° - 158°F (0° - 70°C)
- **Clock power:**
  - PoE/Battery Models: IEEE 802.3 PoE at/af PoE+ (Class 0, 2 Watts Peak, 1 Watt Nominal)
- **Connectivity:**
  - IEEE 802.3 10/100 Base-T Ethernet
- **Security:**
  Encryption: TLS 1.3

DIALS

- Customized clock faces are available to display your organization's name or logo
- Please call for more information



PoE Model

To Learn More:
Call - 855-602-2934
Email - info@primexinc.com
primexinc.com

©2025 by Primex, Inc.
The Primex logo is a registered trademark of Primex, Inc. All Rights Reserved. 5.14.25