Wood Series Analog Clocks

PoE (Power over Ethernet)

Our proven, long-trusted technology synchronizes time across campuses, hospitals, and facilities of any size — enhancing efficiency, reducing delays, and ensuring pinpoint accuracy. With automated daylight saving time adjustments and zero disruption, Primex Sync keeps your organization running on time, all the time.

Primex Sync Wood Series analog clocks are ideal for offices, libraries, conference rooms, and entryways. The solid hardwood frame is available in a variety of finishes, and dial faces are available with Arabic numerals on ivory dials or Roman numerals on antique dials.

Built in PoE means there is no need for additional power source or batteries, as the cable that carries the time data to the clocks also carries power. Primex Sync PoE clocks are delivered preconfigured, ready to quickly access your existing network. Simply take the clocks out of the box, connect to PoE power (Power over Ethernet), and hang them on the wall. Battery backup allows for continued accurate time even when the power goes out.

POE WOOD SERIES ANALOG CLOCKS - POE POWERED WITH BATTERY BACKUP

PART NO.	DESCRIPTION
124-PE150C10	16" (40.64cm) Wood Dark Cherry Wood, Arabic Dial, PoE powered, Configured
124-PE150H10	16" (40.64cm) Wood Honey Finish, Arabic Dial, PoE powered, Configured
124-PE150K10	16" (40.64cm) Clear Oak Finish, Arabic Dial, PoE powered, Configured
124-PE150N10	16" (40.64cm) Wood Walnut Finish Wood, Arabic Dial,PoE powered, Configured



Honey Arabic



Dark Cherry Arabic



Clear Oak Arabic



Walnut Arabic

FEATURES

- Automatically adjusts for Daylight Saving Time
- Clock Lock feature can be used to securely mount to the wall
- Clock configuration to access your network is accomplished online prior to delivery for plug-and-play convenience
- Battery backup allows for continued accurate time even when the power goes out (batteries not included)

Power:
- PoE/Battery Models: IEEE 802.3 PoE at/af PoE+ (Class 0, 2 Watts Peak, 1 Watt Nominal)

Connectivity:
- IEEE 802.3 10/100 Base-T Ethernet

Security:
- Encryption: TLS 1.3

WOOD SERIES SPECIFICATIONS

- Hardwood frame
- Operating range: 32° - 158°F (0° - 70°C)
- **Clock power:**
  - PoE/Battery Models: IEEE 802.3 PoE at/af PoE+ (Class 0, 2 Watts Peak, 1 Watt Nominal)
- **Connectivity:**
  - IEEE 802.3 10/100 Base-T Ethernet
- **Security:**
  Encryption: TLS 1.3

LENS

- Durable thermoplastic lens

DIALS

- Ivory dials have Arabic Numerals
- Antique dials have Roman Numerals
- Customized clock faces are available to display your organization's name or logo. Please call for more information.



PoE Model

To Learn More:
Call - 855-602-2934
Email - info@primexinc.com
primexinc.com

©2025 by Primex, Inc.
The Primex logo is a registered trademark of Primex, Inc. All Rights Reserved. 5.14.25